

# AirSentry® II

Point-of-Use Ion Mobility Spectrometer (IMS)



The AirSentry II family of ion mobility spectrometers detect and alert users to small concentrations or changes in airborne levels of chlorides, acids, amines and ammonia-containing species. With parts-per-trillion (ppt) sensitivity, these point-of-use sensors provide fast response, increased detection selectivity and repeatable performance.

Combining Air Sentry II sensors with a central software platform allows for easy data acquisition and analysis. The AirSentry II family of sensors provide continuous actionable data, to enable efficient response to contamination sources and events.

## BENEFITS

- Continuous AMC monitoring of critical locations
- Robust and reliable data acquisition, control and analysis
- Long-term data stability
- Lowest cost-per-test

## FEATURES

- High-sensitivity detection of acids and bases (amines, ammonia and chlorides)
- Versatile product configuration for point-of-use, multi-point and mobile monitoring applications
- Compact size allows placement in any location
- Ethernet, RS-232, 4-20 mA outputs

## APPLICATIONS

- Real-time corrosion monitoring within etch process locations
- Real-time amine and ammonia monitoring within critical lithography systems
- Quantification of chemical filter efficiency
- Tracking and troubleshooting of contamination sources throughout cleanroom and in process tools
- Analysis of contamination within FOUNDRY wafer storage modules



**PARTICLE  
MEASURING  
SYSTEMS®**  
pmeasuring.com

*Without measurement there is no control*

# AirSentry® II

Point-of-Use Ion Mobility Spectrometer (IMS)

Specifications

<b>Contaminants detected</b>	Individual analyzers to detect Ammonia, Amines, or Acids
<b>Range</b>	0 – 50 ppb <sub>v</sub>
<b>Sample flow</b>	< 1000 cc/min
<b>LDL (3σ)*</b>	70 ppt <sub>v</sub>
<b>Response time</b>	< 5 min to 95% (Dry)
<b>Cleardown time</b>	< 5 min to 5% (Dry)
<b>Temperature range</b>	Operating: 59 – 86 °F (15 – 30 °C) Storage: - 40 – 122 °F (- 40 – 50 °C)
<b>Humidity range</b>	Operating: 30 – 60% RH Storage: 0 – 90% RH
<b>Dimensions (H x W x L)</b>	4 x 9 x 12 in (10 x 23 x 31 cm)
<b>Weight</b>	5 lb (2.3 kg)

\* 5 minute sample averaging, 760 Torr

## Utility Requirements

<b>Power</b>	100 – 240 VAC (50/60 Hz), 60 W
<b>Clean Dry Air (CDA)</b>	< 1000 cc/min, < - 60 °C dew point, 5 psig precision regulated, no particles > 50 µm, hydrocarbon free
<b>Vacuum</b>	< 33 kPa (absolute)

## Communication

<b>Data output</b>	Ethernet (to Facility Net software), RS-232 (to HyperTerminal), 4-20 mA
<b>User interface</b>	4 LEDs, 2 buttons (Zero/Span Calibration)

AirSentry® is a registered trademark of Particle Measuring Systems, Inc.

Patents pending.

Particle Measuring Systems, Inc. reserves the right to change specifications without notice.

### HEADQUARTERS

5475 Airport Blvd  
Boulder, Colorado 80301 USA  
T: +1 303 443 7100, +1 800 238 1801

Instrument Service & Support  
E: +1 800 557 6363  
Customer Response Center  
T: +1 877 475 3317  
E: info@pmeasuring.com

### GLOBAL OFFICES

BRAZIL  
T: +55 11 5188 8227  
E: pmsbrazil@pmeasuring.com

### CHINA

T: +86 21 6113 3600  
E: pmschina@pmeasuring.com

### FRANCE

T: +33 (0)6 82 99 17 98  
E: pmsfrance@pmeasuring.com

### GERMANY

T: +49 6151 6671 632  
E: pmsgermany@pmeasuring.com

### ITALY

T: +39 06 9053 0130  
E: pmsrl@pmeasuring.com

### JAPAN

T: +81 3 5298 8175  
E: pmsjapan@pmeasuring.com

### KOREA

T: +82 31 286 5790  
E: pmskorea@pmeasuring.com

### MEXICO

T: +52 55 2271 5106  
E: pmsmexico@pmeasuring.com

### NORDIC

T: +45 707 028 55  
E: pmsnordic@pmeasuring.com

### PUERTO RICO

T: +1 787 718 9096  
E: pmspuertorico@pmeasuring.com

### SINGAPORE

T: +65 6496 0330  
E: pmsingapore@pmeasuring.com

### TAIWAN

T: 886-3-5525300 Ext: 301  
E: pmstaiwan@pmeasuring.com

### UNITED KINGDOM

T: +44 1684 581 000  
E: pmsemea@pmeasuring.com



**PARTICLE  
MEASURING  
SYSTEMS®**