

Lasair[®] Pro

Aerosol Particle Counter, No Wireless Communication Option

Designed for intuitive and reliable portable particle counting

Without measurement there is no control



For use in ultra-high security cleanrooms, PMS has introduced a Lasair Pro 310 model specifically designed without any radio frequency (RF) wireless communication capabilities. This specific product part SKU will not contain any hardware or firmware to enable Bluetooth, WiFi, or NFC capability and offers the same industry leading features of the PMS Lasair Pro 310 with 1.0 CFM sample rate measuring particles $\geq 0.3 \mu\text{m}$ in up to 8 configurable channels.

The Lasair[®] Pro product line is designed with the latest technology as a complete contamination control solution. The multi-gesture touchscreen interface menu guides users through logical navigation for intuitive learning. Sampling configuration and data handling is efficient and reliable and can be remotely managed over Ethernet or USB data download.

BENEFITS

- Portable, continuous operation
- Easy to clean polycarbonate exterior
- Reduced operator errors with pre-set recipes
- Long-term data archive with DataAnalyst software
- VHP-resistant enclosure and HEPA-filtered exhaust
- Audit trail meets latest data integrity requirements
- Comprehensive validation manual (optional)

FEATURES

- 8.4-inch SVGA color touchscreen compatible with gloves
- 21 CFR Part 11 compliant audit trail with 20,000 recorded activities
- Up to 100 configurable users with three (3) privilege groups (administrator, supervisor, operator)
- Up to 1,000 configurable locations organized by area, room, and location hierarchy
- Up to 100 configurable recipes
- Rechargeable lithium ion batteries for portable use
- Optional thermal printer

APPLICATIONS

- Cleanroom monitoring
- Facility certification for ISO 14644-1:2015, EU GMP, China GMP, FS 209E
- Trend analysis
- Statistical process control
- Troubleshooting particle excursions
- Manifold compatible
- Portable or dedicated use

Contact your local PMS Sales representative

with any questions or to receive a quote as well as for a full Letter of Volatility for any Lasair Pro product line variant.

Lasair[®] Pro

Aerosol Particle Counter, No Wireless Communication Option

Specifications

MODEL	310 (P/N 10141012X)	310 (P/N 10141002X)
Size range	0.3 - 25.0 µm	
Flow rate	28.3 LPM (1.0 CFM) ±5%	
Zero count	< 7.07 counts / m ³	
Maximum concentration ¹	> 42,924,662 / m ³	
Channels	Up to 8 configurable channels. Optional 2-channel pharmaceutical mode.	
Counting efficiency	50% ±20% for most sensitive channel. ISO 21501-4:2018 compliant.	
Tubing length	Maximum 8 meters	
Compressed gas	Air (CDA), Argon (Ar), carbon dioxide (CO ₂), nitrogen (N), or customized density. Requires HPD III accessory.	
Display and printer	8.4-inch color SVGA display, p-cap with finger swipe and gesture control Optional built-in thermal printer with paper cutter. Supports cleanroom paper.	8.4-inch color SVGA display, p-cap with finger swipe and gesture control No printer
Exterior surface	Polycarbonate (PC)	
Data storage	10,000 complete data sets. Data cannot be altered and meets 21 CFR Part 11 compliance.	
Reporting	Encrypted PDF, cleanroom monitoring and certification for ISO 14644-1, EU GMP, China GMP, and FS209E	
Remote operation	Real-time download to Facility Net, Pharmaceutical Net Pro, FacilityPro [®] SMART NG, or FacilityPro SCADA NG software, USB download, automatic clock adjustment with NPT server	
Communications	Ethernet, USB data download	
Input/Output	Four 4-20 mA inputs (<0.5% of Span), four 4-20 mA outputs (<1.0% Span), one 5V pulse output	
Operating environment	Temperature: 0 - 32 °C (32 - 89.6 °F) Humidity: 5 - 95% RH non-condensing	
External dimensions	21.6 x 25.6 x 24.4 cm (8.5 x 10.1 x 9.6 in)	
Weight	6.4 kg (14.2 lb) with two optional batteries 5.4 kg (11.9 lb) without batteries	
Power	100 - 240 V, 50-60 Hz, 2.5 A. Up to two rechargeable Li-ion batteries.	
Laser classification	Class 1, complies with US 21 CFR 1040.10 and EN60825-1. An internal Class 4 laser is used per EN60825-1.	
Calibration	Meets ISO 21501-4:2018 requirements. Optional ISO 17025 compliance available.	

1 Less than 10% coincidence loss at maximum recommended concentration.

SOLUTIONS FOR YOUR INDUSTRY
Scan to learn more about our products!



HEADQUARTERS

Boulder, Colorado 80301 USA
T: +1 303 443 7100

Instrument Service & Support
T: +1 303-443-7100 ext 447

Service and Calibration
E: workorders@pmeasuring.com

Technical Support
E: techsupport@pmeasuring.com

Software or System Support
E: ssupport@pmeasuring.com

Customer Service and Order Processing
E: customerorders@pmeasuring.com

www.pmeasuring.com
info@pmeasuring.com

GLOBAL OFFICES

AUSTRIA
T: +43 512 390 500
E: pmsaustria@pmeasuring.com

BENELUX
T: +32 10 23 71 56
E: pmsbelgium@pmeasuring.com

BRAZIL
T: +55 11 5188 8227
E: pmsbrazil@pmeasuring.com

CHINA
T: +86 21 6113 3600
E: pmschina@pmeasuring.com

FRANCE
T: 33(0)1 60 10 32 96
E: pmsfrance@pmeasuring.com

GERMANY
T: +49 6151 6671 632
E: pmsgermany@pmeasuring.com

ITALY
T: +39 06 9053 0130
E: pmsrli@pmeasuring.com

JAPAN
T: +81 44 589 3498
E: pmsjapan@pmeasuring.com

KOREA
T: +82 31 286 5790
E: pmskorea@pmeasuring.com

MEXICO
T: +52 55 2271 5106
E: pmsmexico@pmeasuring.com

NORDIC
T: +45 707 028 55
E: pmsnordic@pmeasuring.com

PUERTO RICO
T: +1 787 718 9096
E: pmspuertorico@pmeasuring.com

SINGAPORE
T: +65 6496 0342
E: pmsingapore@pmeasuring.com

SWITZERLAND
T: +41 71 987 01 01
E: pmsswitzerland@pmeasuring.com

TAIWAN
T: 886-3-5525300 Ext: 301
E: pmstaiwan@pmeasuring.com



FacilityPro[®] and Lasair[®] are registered trademarks of Particle Measuring Systems, Inc. All other trademarks are the property of their respective owners. Particle Measuring Systems, Inc. reserves the right to change specifications without notice. © 2023 Particle Measuring Systems, Inc. All rights reserved. 04132023